



## Technical data

Performance		XAHS 408 ST V			XAVS 378 ST V		
Nominal effective working pressure	bar(g)	7-8.6	10.3	12	7-10.3	12	14
	psi(g)	100-125	150	175	100-150	175	200
Free air delivery	cfm	847	792	735	778	725	672
	m <sup>3</sup> /min	24	22.4	20.8	22	20.5	19
	l/sec	400	374	347	367	342	317
Max. Ambient temp. at sea level	°C	45			45		
Min. Starting temperature	°C	-10			-10		
Min. Starting temperature (Cold start option)	°C	-25			-25		
Engine							
Engine Brand		Cummins					
Engine Model		B6.7 stage V					
Number of cylinder		6					
Engine power	kW	187			187		
Full load rpm		1750					
Unload rpm		1100					
Emission level		stage V					
Capacity							
Engine oil	l	17					
Compressor oil	l	40					
Fuel tank	l	270					
Noise level							
Sound pressure level (LpA) at 7m	dB(A)	72					
Dimensions and weight: undercarriage							
LxWxH	mm	5650 x 1987 x 2058					
Weight (wet)	kg	3500					



## Options

- Support mounted or skid
- Adjustable towbar
- Jockey wheel
- Towing eyes (DIN, ITA, NATO, BNA, ball coupling and loose ball coupling)
- Road light system
- Fleetlink
- Quality air equipment
  - Aftercooler
  - WSD
  - Bypass valve
  - PD filter
- Special application equipment
  - Inlet shut down valve
  - Spark arrester
- Cold start
- Metal filler neck

